## **NOTES:**

2"X12"X10'

- ALL LUMBER TO BE S 4 S.
- ALL SURFACES TO BE PAINTED WITH 2 COATS OF WHITE PAINT CONFORMING TO SEC. 91-3 OF PLACER COUNTY GENERAL SPECIFICATIONS PRIOR TO APPLICATION OF REFLECTIVE SHEETING.
- ALL LUMBER BELOW GROUND LEVEL AND BARRICADE POSTS SHALL BE PRESSURE TREATED FIR OR HEART REDWOOD.
- NUMBER OF BARRICADES REQUIRED SHALL BE AS SHOWN ON THE PLANS APPROVED BY THE ENGINEER - A MINIMUM OF TWO BARRICADES WILL BE CONSTRUCTED AT THE END OF STREETS.
- ORANGE STRIPE SHALL CONSIST OF REFLECTIVE SHEETING MEETING OR EXCEEDING CALTRANS SPECIFICATIONS FOR TYPE 2 REFLECTIVE SIGN SHEETING (ENGINEER GRADE).
- A "W31(CA)(END)/OM4-3 (RED REFLECTOR)" SIGN SHALL BE INSTALLED BEHIND THE BARRICADE IN LINE WITH THE APPROACHING TRAFFIC.
- ADDITIONAL OM4-3 REFLECTORS AND/OR SIGNS MAY BE REQUIRED ON BARRICADE, BY THE ENGINEER.

- 10'

NOTE 7

SEE

NOTE 5

UUUUUUU

3' MIN.

6"X6"X7' MIN.

## **COUNTY OF PLACER DEPARTMENT OF PUBLIC WORKS**

## **ROADWAY TIMBER BARRICADE**

DATE: JULY, 2005 NTS PLATE **R-24** (45)

DIRECTOR OF PUBLIC WORKS

APPROVED!

