CAPCOA

CALIFORNIA AIR POLLUTION CONTROL OFFICERS ASSOCIATION

CEQA & Climate Change

Evaluating and Addressing Greenhouse Gas Emissions from Projects Subject to the California Environmental Quality Act

January 2008

"average" treatment plant. Thus, research will need to be conducted on a case-by-case basis to determine the "Fraction Anaerobically Digested" which is a function of the type of treatment process. Indirect emissions from these facilities can be calculated using the CCAR energy use protocols and URBEMIS model for transportation emissions.

Solid Waste Disposal Facilities

Air districts will have emission estimate methodologies established for methane emissions at permitted landfills. In addition, EPA's Landfill Gas Emissions Model (LandGem) and the CCAR methodology could also be used to quantify GHG emissions from landfill off gassing; however, this model requires substantial detail be input. The model uses a decomposition rate equation, where the rate of decay is dependent on the quantity of waste in place and the rate of change over time. This modeling tool is free to the public, but substantial project detail about the operation of the landfill is needed to run the model. Indirect emissions from these facilities can be calculated using the CCAR energy use protocols and URBEMIS model for transportation emissions.

Construction Emissions

GHG emissions would occur during project construction, over a finite time. In addition, a project could result in the loss of GHG sequestration opportunity due primarily to the vegetation removed for construction. URBEMIS should be used to quantify the mass of CO_2 that would occur during the construction of a project for land development projects. Some construction projects would occur over an extended period (up to 20–30 years on a planning horizon for general plan buildout, or 5–10 years to construct a dam, for example). OFFROAD emission factors are contained in URBEMIS for CO_2 emissions from construction equipment. For other types of construction projects, such as roadway construction projects or levee improvement projects, SMAQMD's spreadsheet modeling tool, the Road Construction Emissions Model (RoadMod), should be used. This tool is currently being updated to include CO_2 emissions factors from OFFROAD.

The full life-cycle of GHG emissions from construction activities is not accounted for in the modeling tools available, and the information needed to characterize GHG emissions from manufacture, transport, and end-of-life of construction materials would be speculative at the CEQA analysis level. The emissions disclosed will be from construction equipment and worker commutes during the duration of construction activities. Thus, the mass emissions in units of metric tons CO_2e/year should be reported in the environmental document as new emissions.

General Plans

In the short-term, URBEMIS can be used as a calculation tool to model GHG emissions from proposed general plans, but only if data from the traffic study is incorporated into model input. The same methodology applied above in the specific plan example applies to general plans. The CCAR GRP can be used to approximate indirect emissions from