	SE MD MERIDIAN CALIFORNIA
CORNER TYPE: GOVT. CORNER MEANDER TO RANCHO	CONTROL OTHER
CORNER IDENTIFICATION - DATE OF VISIT November 7	_19_80
1 Z	
CORNER - LEFT AS FOUND FOUND AND TAGGED REE	STABLISHED OBLITERATED CORNER THE REBUILT
PHYSICAL DESCRIPTION OF CORNER FOUND; EVIDENCE AND METHOD U	SED TO IDENTIFY OR REESTABLISH
Found twin fir stump with remnants of old	
corner agrees with record to sec. corner	24 & 25 to north and 1/4 17 & 20 to east.
	t on Range Line a 2"x30" aluminum magnetic
survey monument 20" in ground with 34" alu	uminum cap stamped: JAMES F. NICKLOS-LS384
Raised rock mound 48" dia, by 10" high	T17N
Raised rock mound 48" dia. by 10" high WF 9" DBH S19 E 20.4"; scribed S20BT, tags	ged LS3848 R14E R15E
JP 9" DBH N72°E 22.0'; scribed S17BT, tags	ged LS3848 S25 S17 CC
	1980
CALIFORNIA COORDINATE SYSTEM ORDER: FIRST SECON	The state of the s
STATIONS USED: NGS (USC & GS) STATE COUNTY COUNTY	OTHER STATION STATION
	EASI/RUS (A)
SKETCH: (Include reference tie or witness points, remarks and topo	of area)
24	
25	
	Orig. BT:
N00°11'44"E	Fir stump N72°E 249.48' (Record) Fir 20" N72°E 249.48'
326.2/' New BT:	(Record) Fir 20" N/2 E 249.48'
(Record) New BT: (Record) JP 9" DBH N72°E 22.9'	
North 325.38'	N88°57'14"W 1821.85'
0 - 100	ecord) West 1821.60' 17
N88°57'14"W	1/4
10.91 W	
Calculated	position for original 20
Calculated closing con	
8 \	
z \ \	
New BI:	
WF 9" DBH S19°E 20	0.4'
E 1/4 S25	
SURVEYOR'S CERTIFICATE	COUNTY SURVEYOR'S CERTIFICATE
THIS CORNER RECORD WAS PREPARED BY ME OR UNDER MY	THE CORNER RECORD WAS RECEIVED APR 1985
OH April 1. 10 85	AND EXAMINED AND FILED ARR 1985.
En 16 7.	TITLE DEPUTY COUNTY SURVEYOR
Well 01 7 11-600	The state of the s
SIGNED CONTROL OF CONTROL	
L.S. 3848	DOCUMENT No.

SEAL

YES - NO -